

---

## Standard Asphalt Distributor

We at Gaoyuan are an ISO9001:2000 certified standard asphalt distributor manufacturer, based in China. According to different asphalt tank volume, we primarily offer customers three types of asphalt distributor, that is, 4m<sup>3</sup> asphalt distributor, 6m<sup>3</sup> asphalt distributor and 8m<sup>3</sup> asphalt distributor.

### **Features**

1. Gaoyuan standard asphalt distributor is developed on the basis of the internationally advanced technologies and our years of construction and equipment design experience. Hence, it is economical, functional and easy to operate.
2. The adoption of HTF internal heating method enables liquid to run smoothly and prevents asphalt from coke burning.
3. The rotation indicator reads asphalt pump rotation speed. The operator could calculate the corresponding vehicle speed and asphalt rotation speed to different spray volume using our specified formula, thereby helping guaranteeing uniform spray volume.
4. Because all production procedures are strictly inspected by our operators, our standard asphalt distributor is highly reliable and stable.

### **Applications**

Gaoyuan standard asphalt distributor is an indispensable piece of road maintenance equipment designed to spray emulsified asphalt, diluted asphalt, hot asphalt, hot modified asphalt and various binders. It is usually used for dealing with upper and lower seal layer, prime layer, asphalt surfacing, asphalt penetration surface, fog seal layer and so on. Additionally, it can also be used to transport liquid asphalt and other heavy oil.

### **Main Technical Specifications**

#### **4m<sup>3</sup> Asphalt Distributor (Standard Type)**

Product model	HGY5070GLQ
---------------	------------

Chassis model	HFC1080K3T
Spray width	200-4000mm
Spray volume:	0.3-3.0 kg/m <sup>2</sup>
Asphalt tank volume	4000L
Asphalt heating mode	Imported diesel oil burner (calorific value 10×10 <sup>4</sup> kCal/h)
Spray media	hot (modified) asphalt, diluted asphalt, emulsified asphalt, etc.
Overall dimensions	L×W×H=6340×2100×2540 (mm)

### **6m<sup>3</sup> Asphalt Distributor (Standard Type)**

Product model	HGY5120GLQ
Chassis model	ZZ1121G4715C1
Spray width	200-4500mm
Spray volume	0.3-3.0 kg/m <sup>2</sup>
Asphalt tank volume	6000L
Asphalt heating mode	Imported diesel oil burner (calorific value 10×10 <sup>4</sup> kCal/h)
Spray media	hot (modified) asphalt, diluted asphalt, emulsified asphalt, etc.
Auxiliary power/rotation	26kW/2350r/min
Overall dimensions	L×W×H=8700×2496×3350 (mm)

### **8m<sup>3</sup> Asphalt Distributor (Standard Type)**

Product model	HGY5122GLQ
Chassis model	ZZ1121G5311W CNHTC HUANGHE COMMANDER
Spray width	200-4500mm
Spray volume	0.3-3.0 kg/m <sup>2</sup>
Asphalt tank volume	8000L
Burner	G20S, Imported diesel oil burner (calorific value 10×10 <sup>4</sup> kCal/h)
Spray media	hot (modified) asphalt, diluted asphalt, emulsified asphalt, etc.
Auxiliary power/rotation	26kW/2350r/min
Overall dimensions	L×W×H=9250×2496×3450 (mm)

Whether you are looking for a synchronous chip sealer, micro

---

curfacing paver or chip spreader, we at Gaoyuan can help you with all your road matintenance equipment needs. As a result of their consistent quality and reliability, our products are CE certified. To make customers feel secure in their purchase, we back our products with complete services, including stallation, maintenance, repair and operator training services.

Interested in our products? Please don't hesitate to contact us. Our staff is waiting to serve you!

## **FEED BACK FORM**

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address: